

VX2835wm

**28" WIDE (27.5" VIEWABLE)
MULTIFUNCTION LCD**

WITH HDMI FOR HD QUALITY VIDEO

Desktop experience amplified.

ViewSonic's 28" VX2835wm widescreen (27.5" viewable) LCD amplifies your desktop experience. With ultra-fast 3ms response and integrated speakers and amp, the VX2835wm offers high-performance features that elevate your desktop to a whole new level. Work more productively on the EXPANSIVE 27.5" WIDESCREEN DISPLAY. Play more intensely with HD games, movies and videos in their native format. MULTIPLE VIDEO CONNECTIONS including HDMI let you SELECT THE BEST INPUT SOURCE for your digital entertainment. The high 800:1 contrast ratio (typ) and high 500 nits brightness (typ) produce remarkably bright and rich colors. Integrated digital speakers and VESA® wall-mount compliance save space and reduce desktop clutter. The VX2835wm is perfect for the serious gamer and movie aficionado who want a complete digital entertainment experience on the desktop.



WORK FASTER, PLAY SMARTER

- > Full 27.5" viewable widescreen with 1920x1200 resolution
- > True 1080p with HDMI for HD quality video
- > ClearMotiv® 3ms video response time
Fast 3ms video response enables digital, HD broadcast-quality video.
- > Stylish slim-bezel design with glossy, piano-black finish
The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > Multifunction LCD with OptiSync® digital/analog inputs
Digital HDMI input gives you the best possible connection to HD signals for movies, video and games. Multi-mode input technology supports both digital (HDMI or DVI) and analog (VGA) signals.
- > Ultra-high brightness and contrast
500-nit brightness (typ) and 800:1 contrast ratio (typ) for rich, detailed images, videos, and games.
- > Multimedia enhanced
Save desk and workspace and enjoy rich, stereo sound with built-in stereo speakers.
- > OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows Vista approved
- > ENERGY STAR® qualified



HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VX2835wm

28" WIDE (27.5" VIEWABLE) MULTIFUNCTION LCD WITH HDMI FOR HD QUALITY VIDEO



LCD	Type	28" (27.5" viewable) Wide Color TFT Active Matrix LCD
	Display Area	23.4" horizontal x 14.6" vertical; 27.5" diagonal
	Optimum Resolution	1920x1200
	Contrast Ratio	800:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	3ms gray-to-gray (avg); 5ms black-white-black (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	500 cd/m2 (typ)
Panel Surface	Anti-glare	
VIDEO INPUT	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Digital	HDMI (with HDCP), component, composite, S-video
	Frequency	F _H : 24~82kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1920x1200
CONNECTOR	Analog/Digital	15-pin mini D-sub/HDMI
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2x3-watt
	Amp	3-watt
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	64W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select, audio adjust, ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness aspect ratio, opticolor), PIP, PBP, setup menu (language, resolution notice, OSD position, OSD timeout, OSD background, sleep), memory recall
OPERATING CONDITIONS	Temperature	4–131°F (20–55°C)
	Humidity	20–85% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	26.1" x 22.8" x 12.1" (662mm x 578mm x 306mm)
	Physical without stand	26.1" x 19.3" x 3.4" (662mm x 489mm x 87mm)
WEIGHT	Net with stand	26.5 lb. (12 kg)
	Net without stand	18.8 lb. (8.5 kg)
	Gross with stand	31.6 lb. (14.3 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS, TCO'06
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.
POWER MANAGEMENT		Meets TCO'06 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, audio cable, HDMI to DVI-D cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on LCD, parts and labor.



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows Vista logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13363-00B-01/07] VX2835wm-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com