

# Canon

# LV-7250

**List Price: \$1,799.99**

**Item Code:** 1294B002

**UPC Code:** 013803 065169

**Delivery:** Mid April

#### **Kit Contents:**

- LV-7250 Projector
- Remote Control (w/AAA Batteries)
- VGA Computer Cable
- USB Remote Mouse Receiver
- Power Cable
- Soft Carrying Case
- Lens Cap
- Warranty Card



#### **Key Feature List**

- **Genuine Canon Optics: 1.6X Zoom Lens**
- 2000 ANSI Lumens
- Native XGA Resolution (Supports UXGA and SXGA through high-quality compression)
- **Short Throw Distance: Project 100" Screen from only 9.6 feet**
- **Quick Start (8 seconds)** and Quick Cooling (30 seconds)
- **Quiet Operation: Only 29dB**
- **600:1 Contrast Ratio (LV-7250)**
- Long Life Lamp: Up to 3000 hours in Quiet Mode
- Automatic Keystone Correction (+/- 30 degrees Vertical)
- Manual Keystone Correction (+/- 30 degrees Vertical)
- Color Management System – For accurate and precise image adjustment
- Flexible Image Settings – Preset image modes designed to help bring out the best image quality
- **Enhanced Wall Color Correction** (Used for projecting on chalkboards and conference room walls)
- **Improved Control Panel**
- **User-Friendly On-Screen Menu**
- **Automatic Power Off Timer**
- Front or Rear Projection, Ceiling Mount Compatible
- Connect two laptops at the same time
- Excellent Connectivity – Connects with your HDTV, DVD Player, VCR, Digital Camcorder, Document Camera
- Wireless Mouse Control (**Includes Drag & Drop Feature**)
- Size (W x D x H) 12.2 x 10.4 x 4.3 in. (310 x 265 x 109 mm)
- Weight: LV-7250: Approx. 6.6 lbs. (3kg)

#### **Packaging/Shipping Information**

(WxDxH) 17.8 x 16.1 x 12.5 in

Weight: 11.7 lbs (5.3kg)

#### **Canon Customer Support**

- Canons Advanced exchange for the first year (Pro AV / Pro Centre only)
- During the entire 3 year Warranty a loaner projector can be provided if the original is in need of repair.
- 3 Year Parts and Labour Warranty – 120 Day Lamp Life Warranty

#### **Optional Accessories:**

- Replacement Lamp (LV-LP26)
- Ceiling Mount (RS-CL11)
- Component Video Adapter Cable (LV-CA32)
- RS-232C Cable (LV-CA34)

## Specifications:

Product	LV-7255		LV-7250	LV-X8	
Basics	Imaging Device	0.7" LCD panels x 3		0.6" LCD panels x 3	
	Aspect ratio	4:3			
	Native Resolution	XGA	XGA	XGA	
	Brightness	2500 ANSI Lumens	2000 ANSI Lumens	1500 ANSI Lumens	
	Uniformity	85%			
	Contrast	600:1		500:1	
	Keystone (Vertical)	+/- 30 degrees(Auto/Manual)		+/- 30 degrees (Manual)	
Optics	Projection lens	F1.6 - 2.5 , f=17.7 - 28.3 mm			
	Lens shift	9:1, Fixed	8.6:1.4, Fixed		
	Zoom	1.8x manual			
	Focus	Manual			
	Screen size	25" - 300"			
	Projection distance coverage	3.0 – 24.8ft (0.9 – 7.6m) / 100": 8.2 – 12.8ft (2.5 - 3.9m)	3.6 – 28.9ft (1.1 – 8.8m) / 100": 9.5 - 15.1ft (2.9 - 4.6m)		
	Throw Ratio	1.23-1.93:1	1.44-2.25:1		
Image Adjustments	Color Mode	Presentation, Video, Cinema, Standard, sRGB, custom	Presentation, Video, Cinema, Standard, sRGB		
	Color Adjust	RGB Manual			
	Wall Correction	Auto			
	Mounting	Ceiling/Rear/Ceiling and Rear			
	Tilt Angle	Adjusting feet up to 10 degrees			
Input Signals	Analog PC input	UXGA/SXGA/XGA/SVGA/VGA			
	Scanning frequency	H:15 ~ 100 kHz , V: 50 ~ 100 Hz, Dot clock: 108 MHz			
	Video/S-video input	NTSC/PAL/SECAM/NTSC4.43/PAL-M/PAL-N/PAL-60			
	Component input	1080p/1080i/720p/575p/575i/480p/480i	1080i/720p/575p/575i/480p/480i		
Terminals	Input	Mini D-sub 15pin	Analog PC input /Component input x 2		Analog PC input /Component input x 1
		RCA x1	Video input		
		RCA x2	Audio input		
		Mini DIN 4pin	S-Video input		
		Stereo mini jack	Stereo audio input		
	Output	Mini D-sub 15pin	Analog PC output		
		RCA x2	Audio output	-	-
		Stereo Mini Jack	Audio output	Audio output	-
	Build-in Speaker	1W (Mono)			
Control Terminal	RS-232C				
Lamp	Type	200W NSH	190W NSH	150W NSH	
	Lamp Life(Quiet/Normal)	3000/2000 Hours	3000/2000 Hours	4000/3000 Hours	
Remote Control	Wireless	Wireless Infrared, Front/Back			
	Mouse Control	Mouse control Receiver(USB) w/ Drag and Drop		None	
Ratings	Fan noise (Normal/Quiet)		35/30 dB	35/29 dB	32/25 dB
	Power	Consumption(Normal/Quiet /Stand-by)	275/210W/8W	280/225W/8W	215/180W/8W
		Voltage	AC 100 to 240V , 50/60Hz		
	Temperature	Operating	41 to 104 F (5 to 40 C)		
		Storage	-14 to 122 F (-10 to 50 C), 20%RH ~ 80%RH		
	Dimensions (W x D x H)		11.7 x 10.8 x 4.3 in. (298 x 273 x 110 mm)	12.2 x 10.4 x 4.3 in. (310 x 265 x 109 mm)	
Weight		7.3 lbs (3.3 kg)	6.6 lbs (3.0 kg)	6.4 lbs (2.9kg)	