

# 5500 LUMENS ● WXGA ● MULTI-FUNCTION PROJECTOR

## PLC-WM5500 / 5500L

### WXGA MULTI-FUNCTION PROJECTOR



#### WIDE ASPECT AND HIGHEST BRIGHTNESS

Wide XGA resolution makes it possible to project both HD video contents and wide aspect PC without any setting adjustment. PLC-WM5500/L has an HDMI terminal which is the most popular terminal for video sources. Its higher light efficiency and superior cooling technology allows for the highest brightness (5500 Lm) in its class.

#### FLEXIBLE INSTALLATION

This unit is Equipped with power vertical and horizontal lens shift/keystone correction. Also 5 lens options\* along with the standard lens make this a very flexible projector.

\*PLC-WM5500 includes a standard lens (LNS-S20)

#### EASY MAINTENANCE - ACTIVE MAINTENANCE FILTER

The well-known AMF system detects air blockage or clogs, then advances the filter reel to the next clean filter on the cartridge. Each cartridge carries 10 filter slides which dramatically lowers maintenance.

#### DURABLE IN-ORGANIC OPTICAL SYSTEM (D.I.O.S.)

This Inorganic Optical LCD panel system provides a more durable projector to handle many applications for high-quality, high contrast image presentations.

#### PICTURE IN PICTURE (P in P), PICTURE BY PICTURE (P by P)

This function make it possible to project two different sources with one projector. Video conference, satellite lecture type of application should be suitable with using this function.

#### MECHANICAL SHUTTER SYSTEM

The amazing PLC-WM5500/L fills the needs of a host of demanding business venues including meeting, entertainment and promotional applications with a Mechanical Shutter System.

#### CLOSED CAPTION

The PLC-WM5500/L is Closed Caption compatible.

#### LENS OPTIONS

Model	Type (Zoom)	U/D Ratio	Throw Ratio	F Stop
LNS-W21	Short (Fixed)	1:1 +/-0%	0.8:1	2.0
LNS-W20	Short (x1.3)	11:-1- -1:11 +/-60%	1.3-1.7:1	1.8-2.3
LNS-S20	Standard (x1.7)	11:-1- -1:11 +/-60%	1.7-2.8:1	1.7-2.3
LNS-T20	Long (x1.6)	11:-1- -1:11 +/-60%	2.8-4.6:1	1.8-2.3
LNS-T21	Ultra Long (x1.6)	11:-1- -1:11 +/-60%	4.6-7.2:1	1.8-2.3

#### PRESENTATION TECHNOLOGIES

21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax: 818-717-2719  
 www.sanyoprojectors.com



Resolution	WXGA (1280 x 800)	
Brightness (typical)	5500 Lm	
Contrast Ratio	800:1	
Image Size	40" - 400"	
Aspect Ratio	16:10	
Projection Lamp	330W	
Scanning Frequency	H:15-100kHz, V:48-100Hz	
Fan Noise	31 dBA (eco)	
Voltage	100-240V	
Power Consumption	490W(Normal), 406W (Eco)	
Input signal compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC, 1080p(50/60), 1080i(50/60), 1080-24/25/30 pfs, 720p(50/60), 575p/i, 480p/i	
Color System	NTSC, PAL, SECAM, NTSC4.43, PAL-M/N	
Up / Down Ratio	U/D : +/- 60%, L/R +/- 10%	
Digital Keystone Correction	V +/- 40° , H +/- 20°	
Speaker Output	7W	
Weight (lbs)	21.3 lbs / 19.6 lbs (without Lens)	
Dimensions (inch) W,H,D	19.3"x6.5"x14.6" (without Lens)	
Replacement Lamp	# 610 346 9607	
Replacement Remote	# 645 103 0191	
Replacement AMF Cartridge	POA-FIL080	
Lamp Life * (hour)	3000h (Eco)	
Input	PC/Video	HDMI(1.3b) x 1 (Digital RGB) D-sub 15 x 1 (RGB, Scart RGB) 5BNC x1 (G B R H/V V) (Video/Y Pb/Cb Pr/Cr) Mini DIN 4pin x 1 (S-Video) RCA x 1 (Composite Video, Y) RCA x 2 ( Pb/Cb, Pr/Cr)
	Audio	(HDMI x1) Stereo mini jack x 2 RCA x 2 (R/L-mono)
Output	PC/Video	D-sub 15 x 1 (Monitor out)
	Audio	Stereo mini jack x 1 (Audio out, variable)
Other Feature	D-sub 9-pin x 1 (Control port) RJ-45 x 1 (Wired LAN) Mini jack x 1 (Wired R/C) USB (type B) x 1	
Included Accessories	Power cord VGA cable Lens mount cover Remote control AAA battery x2	Quick reference guide Owner's Manual (CD-Rom) PIN code label
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

\* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



Back Panel