

PLV-Z3000 TopazReal HD

**16:9 Full HD, High Contrast
Home Entertainment Projector**



- Color not exactly as shown -

FULL HIGH-DEFINITION RESOLUTION – 1080p

Not only is it full HD (1920 x 1080), the PLV-Z3000 achieves deep, rich, and very importantly, accurate color. This is automatically accomplished thanks to SANYO's exclusive TopazReal HD Technology, a 3D color management system that addresses color phase and color level to obtain perfect color reproduction. The PLVZ300's color management system can generate a total of approximately 216 billion possible color combinations. This new color management system was designed to optimize the potential of deep color from either of the projector's two HDMI inputs.

LENS MAXIMIZATION OF IMAGE DETAIL

Rated at 1200 lumens, the PLV-Z3000 is capable of an incredible 65,000:1 contrast ratio for superlative black levels, even in ambient light. Plus it has a newly-developed, high-efficiency lens that maximizes image details for exceptional optical performance.

ADVANCED LENS SHIFT FOR VARIOUS ROOM ENVIRONMENTS

The PLV-Z3000 is outfitted with the industry's most advanced lens shifting function. When coupled with the projector's short throw capability and 2x zoom, the PLVZ3000 can create a large screen image in any size room and from virtually any location. The lens shifting function allows wide-range shifting up or down to three screen sizes and left to right to two screen sizes. The throw design of the PLV-Z3000, which is capable of projecting a 100-inch diagonal image from 10 to 20 feet away, makes it extremely suitable for small to mid-size home theaters.

VIRTUALLY SILENT FAN DESIGN

A 1200 lumen projector generates a tremendous amount of heat and requires a high quality fan to ensure proper operation. At this level of brightness, the fan is 'on' most of the time and the noise can be extremely loud and disruptive, especially in smaller home theaters where the projector and the audience are in the same vicinity. To promote greater enjoyment of the film and to reduce noise levels during quiet passages of a film, the PLV-Z3000 is equipped with the industry's quietest fan, a large aperture, low noise Sirocco cooling fan that never rises above 19dB in the economy mode.

50:50 Pulldown Mode

Cinema Color Filter ; 7 Video Mode



PRESENTATION TECHNOLOGIES



1-300 Applewood Cres.,
Concord, Ont. L4K 5C7
Tel 905-760-9944
www.sanyo.ca

Specifications

Resolution	1920 x 1080
Brightness (typical)	1,200 ANSI Lumens
Uniformity	85% (corner to center)
LCD Panel System	0.7" TFT Poly-Silicon x 3 (16:9)
Number of Pixels	6,220,800(2,073,600 x 3)
Contrast Ratio	65000:1 (vivid mode)
Projection Image (diag.)	40" ~ 300"
Aspect Ratio	16:9
Throw Distance	3.9' ~ 60.4'
Zoom/Focus	1x to 2.0x, Manual driven
Lens Shift	Manual (Up/ Down/Left/Right)
Up/Down/Left/Right Ratio	Up/Down: 3: -1 ~ -1:3 (-1V/Center/+1V) Left/Right: 10:0 ~ 0:10 (-0.5H/Center/+0.5H)
Digital Keystone Correction	No
Projection System	Dichroic mirror & 4P prism system w/ PBS
Projection Lens	F2.0 ~ 3.0 / f0.9" ~ 1.8"
Lens Throw Ratio	1.35 ~ 2.7:1
Projection Lamp	165W UHP
Scanning Frequency	H: 15-80kHz, V: 50-100Hz (auto sense/select)
Dot Clock	100MHz (Analog RGB / Component)
HDTV signal	480i/480p/575i/575p/720p/1080i/ 1080p (HDMI/Component)
Color System	PAL/SECAM/NTSC/NTSC4.43/PAL-M/PAL-N
Computer Compatibility	WXGA/SXGA/XGA/SVGA/VGA/MAC
Voltage	100V-240V AC; 50/60Hz (auto voltage)
BTU Rating	839 / 638 (Eco mode)
dB Rating	19dB(A Eco mode)
Power Consumption	246W / 187W (Eco mode)
Dimensions (WxHxD)	15.7" x 5.7" x 13.6" (not including protrusion)
Net Weight	16.5lb
User Maintenance	Clean air filters, replace lamp assembly
Input Terminals	
Component Video 1	Y, Pb/Cb, Pr/Cr (RCA x 3)
Component Video 2	Y, Pb/Cb, Pr/Cr (RCA x 3)
S-Video	S-Video (Mini DIN 4-pin x 1)
Composite Video	Video (RCA x 1)
Computer	Analog RGB (D-Sub 15)
HDMI 19-Pin DVI	HDMI (19-pin Ver.1.3b) x 2
Communication	RS-232C/ Service Port (Mini DIN 8-pin)
Included Accessories	Owner's Manual(Quick manual & CD ROM) ● Illuminated Infrared Remote Control ● AC Power Cord (6.6') ● 2 AA batteries ● Air blower
Optional Accessories	● 610 336 5404 – Replacement Lamp ● POA-MCSRL – Serial Control Cable
FCC Rating	Class B, UL Listed
Warranty	3-years parts & labor; 1 year or 500 hrs lamp (original);

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Illuminated Remote Control



Rear Panel Terminals



Motorized Front Door