



# Cine5000

WIDESCREEN HOME THEATER PROJECTOR  
WITH DARKCHIP2™ DLP® TECHNOLOGY



## Optional Accessories

- Rolling soft case and laptop bag . . . . .PRJ-SCA-004
- Replacement lamp . . . . .RLC-022
- Universal ceiling mount kit . . . . .WMK-005
- Extended Express Exchange® . . . . .PRJ-EE-10-03
- 1m HDMI cable . . . . .DS-QVS-HDMI-1M
- 2m HDMI cable . . . . .DS-QVS-HDMI-2M
- 3m HDMI cable . . . . .DS-QVS-HDMI-3M

<b>PROJECTOR</b>	Type	0.65" DarkChip2™ Digital Micromirror Device (DLP®)
	Pixel Format	1280x768 (native resolution)
	Lens	Manual zoom/manual focus
	Zoom Factor	1.2
	Keystone	Vertical ± 16°, Horizontal ± 7°
<b>DISPLAY</b>	Size	33"–255" (diagonally)
	Throw Distance	59"–394"
	Throw Ratio	1.74–2.09:1
	Lamp	250W, 2,000 hours*
	Brightness	1,000 ANSI lumens
	Contrast Ratio	2000:1
	Aspect Ratio	16:9 (native), 4:3
	Color Wheel	6 segment (RGB RGB)
<b>INPUT SIGNAL</b>	Video	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 720p, 1080i)
	Frequency	F <sub>H</sub> : 15–82kHz; F <sub>V</sub> : 50–85Hz
<b>COMPATIBILITY</b>	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
<b>CONNECTOR</b>	RGB (input)	DB-15 (x1)
	HDMI (input)	HDMI (x1) – HDCP compliant
	Video (input)	RCA jack (x1)
	S-Video (input)	Mini-DIN 4-pin (x1)
	Component Video (input)	RCA jack (x3)
	Screen Relay (12V)	DC power jack
	Audio (output)	Mini-Jack (x1)
<b>POWER</b>	Voltage	90–240 VAC, 50/60Hz (universal)
	Consumption	360W (typ)
<b>CONTROLS</b>	Basic	Standby, menu, input, reset, H/V keystone
<b>OPERATING CONDITIONS</b>	Temperature	41–95°F (5–35°C)
<b>NOISE LEVEL</b>	Humidity	5–95% (non-condensing)
	Normal	36 dB (max)
<b>DIMENSIONS (W x H x D)</b>	Whisper Mode	35 dB (max)
	Physical (mm)	332.7mm x 121.9mm x 294.6mm
<b>WEIGHT</b>	Physical (in.)	13.1" x 4.8" x 11.6"
	Net	10 lb. (4.5 kg)
<b>REGULATIONS</b>	Gross	16.5 lb. (7.5 kg)
<b>CONTENTS</b>	UL/C-UL, FCC-B, TUV, CB, CCC	
<b>WARRANTY</b>	Projector, composite audio/video cable, S-video cable, RGB/DVI cable, power cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with user guide), soft case	
	Three-year limited warranty on parts and labor, first-year Express Exchange® Service. 90-day limited warranty on lamp**	

**ViewSonic®**   
the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Running whisper-mode exclusively can extend lamp life. \*\*Visit ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. DLP™ is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13096-00B-08/06] Cine5000-1

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)